

Product Data Sheet SORB®XT 10L Bucket

Article	SORB®XT 10L Bucket
Article No.	100200
Dimensions (mm)	290x200x260
Weight	1,90 kg
Absorption capacity	approx. 4,00 l per kg



Product Information:

Recommended use

mobile protection for smaller leakages

Application

- spread out SORB®XT evenly over the leaked substance
- work into the material (use mechanical tool, such as a broom, a shovel, Peko XT PLUS by SORB® or a dredge)
- fields of application: plants, companies, environment protection, traffic, municipals, on water/streets/asphalt, usual grounds, industrial grounds, special grounds

After application

- skim off or sweep up the substance from the surface
- dispose of the contaminated material following the respective valid laws and local regulations

Storage

- store in an dry place with low humidity to avoid mold
- store in resealable container or bag

Properties

- Multi-absorbent, grain size 0.125 4.0 mm, 100% organic, floatable binder, type I, II, III-R, SF
- hydrophobic/oleophilic, bulk density approx.
 175 g/l, acts within seconds, highly efficient
- harmless to humans, animals and the environment
- for scattering and absorbing hazardous substances
- absorbs substances such as oil or oil-like substances, fuels, a large number of acids, lubricants, paints, non-stabilised emulsions, brake fluids, coolants, antifreeze, aerosols, alkalis









